



NOTES:

- | | | | | | | | |
|---|--|---------------|----------|--------------------|-----------|-----------------------|----------------|
| <p>1. CASTING SPECIFICATIONS: ASTM A-48 WITH A MINIMUM TENSILE STRENGTH OF 25 KSI (CLASS 25).</p> <p>2. ALL CASTINGS TO BE DIPPED IN ASPHALT BASED PAINT (OR APPROVED EQUAL).</p> | <p>3. CASTINGS SHALL BE AS SPECIFIED BELOW OR EQUAL:</p> <table border="0"> <tr> <td>MANUFACTURERS</td> <td>CAT. NO.</td> </tr> <tr> <td>NEEHAH FOUNDRY CO.</td> <td>R-1740-D2</td> </tr> <tr> <td>CONSTRUCTION CASTINGS</td> <td>J-1425 (SHOWN)</td> </tr> </table> | MANUFACTURERS | CAT. NO. | NEEHAH FOUNDRY CO. | R-1740-D2 | CONSTRUCTION CASTINGS | J-1425 (SHOWN) |
| MANUFACTURERS | CAT. NO. | | | | | | |
| NEEHAH FOUNDRY CO. | R-1740-D2 | | | | | | |
| CONSTRUCTION CASTINGS | J-1425 (SHOWN) | | | | | | |

36" x 24" DOUBLE RING AND COVER